

Declaration of Performance (DoP)

No. C31-CPR-140522			
Product Type:	Insert appliance		
Type, batch or serial number:	Jøtul C 31 and C 33		
Intended use of the product:	Casett (Insert) burning solid fuel without water supply Fuel type: Wood		
Name and Address of the manufacturer:	Jøtul AS		
	Postboks 1411, 1602 Fredrikstad, Norway		
	Tel.: +47 69 35 90 00		
	E-mail: post@jotul.no		
	, ,		
AVCP: System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3		
Notified body:	SP Swedish Natioanal Testing and Research Institute		
NB-No:	402		
Test report no:	P5 04665-E		
Declared performance:			
Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007		
Essential characteristics	Performance		
Fire safety			
Reaction to fire	A1		
Distance to combustible materials	Minimum distances, in mm		
	Floor = 100		
Risk of burning fuel falling out	Combustable materials inside the surround must becovere by insulation as decriebed in the manual		
Emission of combustion products	CO [0,20 %]		
Surface temperature	Pass		
Electrical safety	-		
Cleanability	Pass		
Maximum water operating pressure Flue gas temperature at nominal heat output	- T [355°C]		
Mechanical resistance (to carry a chimney/flue)	NPD		
Thermal output	10.5		
Normal heat output	7 kW		
	- kW		
ROOM DEATING OUTDUIT			
Room heating output Water heating output	-*kW		

Dec	lar	ati	or	1

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Tom J. Berglind

R&D Manager

(Name and function)

Fredrikstad, May 22th 2014

(Place and date of issue)

(Signature)